

# SENSCREEN

1% 3% 5%



Our Senscreen fabrics provide a comfortable, energy efficient environment that blocks up to 95% of UV rays while maintaining natural sunlight and allowing an outdoor view. The perfect and simple solution for controlling heat and glare in any given room.


## SPECIFICATIONS

- **Product Type:** 1%, 3%, 5% Screen
- **Applications:** Roller Shades, Panel Blinds
- **Width:** 118 inches
- **Roll Size:** 118 inches x 30 yards (WxL)
- **Fire Retardant:** NFPA 701-2010 Small Scale Test


- **Composition:** 30% Polyester / 70% PVC
- **Weave:** 2x2 Basket Weave
- **Openness Factors:** 1%, 3%, or 5%
- **Thickness (mm) & Weight (oz/yd<sup>2</sup>):**
  - 1% Openness: 0.67 mm ± 5%, 14.16 oz/yd<sup>2</sup> ± 5%
  - 3% Openness: 0.59 mm ± 5%, 13.57 oz/yd<sup>2</sup> ± 5%
  - 5% Openness: 0.53 mm ± 5%, 12.68 oz/yd<sup>2</sup> ± 5%

- **Cutting:** Ultrasonic recommended, Crush, Cold, Rotary Blade
- **Welding/Bonding Tape:** No
- **Railroading:** Subject to testing
- **Warranty:** 5 years


- **Care & Cleaning Instructions:** Dust can be removed from the fabric by vacuum cleaning or soft duster. Light stains can be removed by gently wiping with a damp cloth or sponge. Do not use detergents, solvents, or scrub against the fabric because it will damage the coating of the fabric. Allow fabric to air dry completely before rolling it back up.
- Color variances may occur between fabric production batches. These variances are within industry tolerances, kindly check fabric prior to cutting.




WHITE 2073




WHITE+BEIGE 2002




WHITE+GREY 2003




BEIGE+GREY 2005




GREY 2006



BLACK+GREY 2007



BLACK+COPPER 2008A



BLACK 2009